

Verification Certificate

This is to certify that:

Centurion Safety Products Limited
Howlett Way
Fison Way Industrial Park
Thetford
IP24 1HZ
United Kingdom

Holds Certificate Number:

VC 684765

In respect of:

**ANSI Z89.1:2014, ANSI Z87.1:2015 and CSA Z94.1-2015
Industrial Safety Helmets**



For and on behalf of BSI:

Shahm Barhom, Group Product Certification Director

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 1 of 28

Verification Certificate

No. VC 684765

Product Specification

Range: Nexus Core/Secure Plus

Product Description: This helmet shell is made of ABS and the model comes in vented and non-vented variants. Nexus Core/Secure Plus is fitted with a 6 point Terylene webbing cradle which is available with slip ratchet or wheel ratchet LDPE headband adjustment and a Dry-Tech (Polyester) sweatband. Nexus Core may optionally be fitted with a 2 point or 4 point adjustable chin strap.

Shell:	ABS, vented and non vented versions
Suspension:	
Cradle:	6 point Terylene webbing
Headband:	LDPE with fitted sweatband
Sweatband:	Dry-Tech (Polyester)
Adjustment system:	Wheel ratchet or slip ratchet
Chinstrap:	EN 397 2 point chinstrap or 4 point chinstrap
Size:	51-63 cm

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Nexus Core/Secure Plus, non-vented	
Classification:	ANSI Z89.1:2014	
	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
	Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.
	LT	Lower temperature (−30°C)

Test Report: BSI 253/8524498 Issue 3, Intertek 102678220CRT-001

Models in Range:	Product code	Description
	S16E*R	Nexus Core, wheel ratchet
	S16E*A	Nexus Core, slip ratchet
	S16E*RL	Nexus Secure Plus, wheel ratchet, EN 397 4 point chinstrap
	S16E*L	Nexus Secure Plus, slip ratchet, EN 397 4 point chinstrap

Notes: * denotes the helmet shell colour
All variants can have brand information presented on a padprint (P) or label (L)
Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Nexus Core/Secure Plus, vented	
Classification:	ANSI Z89.1:2014	
	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
	Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.
	LT	Lower temperature (−30°C)

Test Report: BSI 253/8535351 Issue 3

Models in Range:	Product code	Description
	S16E*RF	Nexus Core, wheel ratchet
	S16E*F	Nexus Core, slip ratchet
	S16E*LF	Nexus Secure Plus, slip ratchet, EN 397 4 point chinstrap

Notes: * denotes the helmet shell colour
All variants can have brand information presented on a padprint (P) or label (L)
Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Nexus Core/Secure Plus, vented	
Classification:	CSA Z94.1-2015	
	Type I	Headwear that provides impact and penetration protection for the crown only.
	Class C	Headwear that does not provide dielectric protection
Test Report:	Colts Z-CTR111816-01	
Models in Range:	Product code	Description/Classification
	S16E*RLF	Nexus core/Secure Plus, wheel ratchet, EN 397 4 point chinstrap Vented.
	S16E*RLFN	Nexus core/Secure Plus, wheel ratchet, EN 397 4 point chinstrap and S30NHIRS reflective stickers, Vented.
Notes:	All variants can have brand information presented on a padprint (P) or label (L)	
Spares and Accessories:	Product code	Description
	S30LY	4 point quick release EN 397 Black Chinstrap (Unbranded)
	S33/35	Suspension with Premium "Twist2Fit" Wheel Ratchet and Dry-Tech sweatband
	S55	Nexus Visor Frame
	S800	Nexus General Purpose Visor Z87+ D3
	S810	Nexus Multi-Purpose Visor Z87+ D3
	S589	Nexus Clear Spectacles Z87+ U6
	S589SE	Nexus Smoke Spectacles Z87+ U6 L1.3

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification

Range: Nexus High Heat

Product Description: Nexus High Heat is made of Polymid GF Nylon and LDPE masterbatch. The model comes in non-vented variants, is fitted with a 6 point Terylene webbing cradle with wheel ratchet LDPE headband adjustment and a Vabon sweatband. Nexus High Heat may optionally be fitted with a 2 point or 4 point adjustable chin strap

Shell:	Polymid GF Nylon and LDPE masterbatch
Suspension:	
Cradle:	6 point Terylene webbing
Headband:	LDPE with fitted sweatband
Sweatband:	Vabon
Adjustment system:	Wheel ratchet
Chinstrap:	2 Point Fixing or 4 Point Fixing
Size:	52-64 cm

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Nexus High Heat, non-vented	
Classification:	ANSI Z89.1:2014	
	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
	Class G	Class G helmets are intended to reduce the danger of contact with low voltage conductors. Test samples are proof-tested at 2,200 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.
Test Report:	BSI 3276218, Intertek 104445692CRT-001	
Models in Range:	Product code	Description
	S22PLUS*R	Nexus High Heat, non-vented, wheel ratchet
Notes:	* denotes the helmet shell colour	
	All variants can have brand information presented on a padprint (P) or label (L)	
	Secure Plus formerly known as Linesman	

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories:	Product code	Description
	S30E	Elasticated 2 point chin strap
	S30L	Leather Chinstrap
	S30LY	4 point quick release EN 397 Secure Plus Black Chinstrap (Branded)
	S30NLNY	S30NY replaceable 4 point adjustable EN 12492 Blue Chinstrap and S30NL Liner to convert Nexus Core to Heightmaster (vented shell only)
	S31D	Dry-Tech sweatband
	S31N	Brushed Nylon Sweatband
	S31P	PVC Sweatband
	S31vK	Vabon sweatband standard
	S33/12	Terylene Cradle with Ratchet and Vabon sweatband Std
	S33/34	Terylene Cradle with Dry-Tech Sweatband
	S33/35	Terylene Cradle with wheel ratchet and Dry-Tech Sweatband
	S50UFL	Universal Fleece Liner
	S50HVOFC	Frost Cape HV Orange
	S50HVFYFC	Frost Cape HV Yellow
	S50HVOEDFC	Frost Cape HV Orange with Ear Defender Compatibility
	S589	Retractable eyeshield Clear, Z87 U6
	S589SE	Retractable eyeshield Smoke Grey, Z87 U6 L1.3
	S55	Contour Visor Carrier
	S800	Contour X General Purpose Facescreen 2C-1,2 1BT 3 9
	S810	Contour XI Multi-Purpose Facescreen 2C-1,2 1BT 3 8-1-0 9
	S30*NHIRS	High Intensity Reflective Stickers (* denotes colour)

Notes:

- * denotes the helmet shell colour
- All variants can have brand information presented on a padprint (P) or label (L)
- Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Range: Nexus Heightmaster

Product Description: This helmet shell is made of ABS and the model is vented. Nexus Heightmaster is fitted with a 6 point Terylene webbing cradle which is available with wheel ratchet LDPE headband adjustment and a Dry-Tech (Polyester) sweatband. Includes a liner for impact and penetration protection

Shell:	Micro peaked, ABS vented shell
Liner:	EPS (Expanded Polystyrene)
Suspension:	
Cradle:	6 point Terylene webbing
Headband:	LDPE with fitted sweatband
Sweatband:	Dry-Tech (Polyester)
Chinstrap:	EN 12492 4 point chinstrap fitted
Size:	53-63 cm

Classification: ANSI Z89.1:2014

Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.
LT	Lower temperature (−30°C)

Test Report: BSI 253/8535017 Issue 3

Models in Range:

Product code	Description
S16E*FMR	Nexus Heightmaster, vented

Notes:

- * denotes the helmet shell colour
- All variants can have brand information presented on a padprint (P) or label (L)

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 9 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories:	Part Number	Item
	S30NY	Heightmaster 4 point adjustable EN 12492 Blue chinstrap
	S30NL	Heightmaster EN 12492 Liner
	S30NLNY	4 point adjustable EN 12492 Blue chinstrap & S30NL Heightmaster Liner
	S31D	Dry-Tech sweatband
	S33/34	Terylene Cradle with Dry-Tech Sweatband
	S33/35	Terylene Cradle with wheel ratchet and Dry-Tech Sweatband
	S589	Retractable eyeshield Clear, Z87 U6
	S589SE	Retractable eyeshield Smoke Grey, Z87 U6 L1.3
	S565	Euro accessory clip
	S71CE	Scala X Ear Defenders
	S72CE	Scala XI Ear Defenders
	S55	Contour Visor Carrier
	S810	Contour XI, anti-fog, clear polycarbonate face screen, Z87+ D3
	S30*NHIRS	High Intensity Reflective Stickers (* denotes colour)

Notes:

- * denotes the helmet shell colour
- All variants can have brand information presented on a padprint (P) or label (L)
- Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Nexus Heightmaster Elec															
Range:	S16 Nexus Heightmaster Elec (Non vented)															
Product Description:	<p>The S16 Nexus Heightmaster Elec, non vented with micro peak is fitted with a 6 point Terylene webbing cradle which is available with wheel ratchet LDPE headband adjustment and a Dry-Tech (Polyester) sweatband. Includes a liner for impact and penetration protection, and a replacement 4-point adjustable chinstrap. S16E*MR is fitted with a 4 point adjustable chin strap.</p> <table><tr><td>Shell:</td><td>Micro Peaked, ABS non vented shell</td></tr><tr><td>Liner:</td><td>EPS Expanded Polystyrene</td></tr><tr><td>Cradle:</td><td>6 Point Terylene webbing</td></tr><tr><td>Headband:</td><td>LDPE (Low Density Polyethylene)</td></tr><tr><td>Sweatband:</td><td>Dry-Tech (Polyester) or Active Comfort sweatband</td></tr><tr><td>Chinstrap:</td><td>Polyester and Acetal Clips</td></tr><tr><td>Size:</td><td>53-63 cm</td></tr></table>		Shell:	Micro Peaked, ABS non vented shell	Liner:	EPS Expanded Polystyrene	Cradle:	6 Point Terylene webbing	Headband:	LDPE (Low Density Polyethylene)	Sweatband:	Dry-Tech (Polyester) or Active Comfort sweatband	Chinstrap:	Polyester and Acetal Clips	Size:	53-63 cm
Shell:	Micro Peaked, ABS non vented shell															
Liner:	EPS Expanded Polystyrene															
Cradle:	6 Point Terylene webbing															
Headband:	LDPE (Low Density Polyethylene)															
Sweatband:	Dry-Tech (Polyester) or Active Comfort sweatband															
Chinstrap:	Polyester and Acetal Clips															
Size:	53-63 cm															
Classification	ANSI Z89.1:2014															
	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.														
	Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.														
	LT	Lower temperature (−30°C)														
Test Report:	BSI 253/8524498 issue 3															
Models in Range:	Product code	Description														
	S16E*A	Nexus Heightmaster Elec (Non vented)														
Notes:	<p>All variants can have brand information presented on a padprint (P) or label (L) * denotes the helmet shell colour</p>															

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories:	Item
	Heightmaster 4 point adjustable EN 12492 Grey Harness
	Heightmaster EN 12492 Liner
	S30NY replaceable 4 point adjustable EN 12492 Blue Harness and S30NL Liner to convert Nexus Core to Heightmaster (vented shell only)
	Dry-Tech sweatband
	Terylene Cradle with Dry-Tech sweatband
	Terylene Cradle with Premium “Twist2Fit” Ratchet and Dry-Tech sweatband
	Retractable eyeshield Clear 2C-1,2 1F UV filter
	Retractable eyeshield Smoke Grey 5-3,1 1F Sunglare filter
	Euro accessory clip
	Visor Carrier
	Contour Visor Carrier
	Contour X General Purpose Facescreen
	Contour XI Multi-Purpose Facescreen 2C-1,2 1BT 3 8 9
	High Intensity Reflective Stickers

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 12 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Range:	Concept
Product Description:	Safety Helmet with two peak styles, the S09 with a 'standard' peak and the S08 with a 'reduced' peak. For versions complying with ANSI Z89.1:2014, there are a number of variations in the build standard of the product, see details below. The range can be fitted with a number of different accessories that are attached via either the Connect or the Euro accessory clips
Shell:	ABS, vented and non vented versions
Suspension:	
Cradle:	6 point Terylene webbing
Headband:	LDPE with fitted sweatband
Sweatband:	Dry-Tech (Polyester)
Adjustment system:	Wheel ratchet or slip ratchet
Chinstrap:	EN 397 2 point chinstrap or 4 point chinstrap
Size range:	Wheel Ratchet headband: 52-64 cm Slip Ratchet headband: 51-63 cm

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Concept, non vented
Classification:	ANSI Z89.1:2014
Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.
LT	Lower temperature (−30°C)

Test Report: UK models BSI 253/8666304, Intertek 102945793CRT-003
KSA models BSI 253/8665698 issue 2, Intertek 102945793CRT-001

	Product code	Description
Models in Range	S08C*A	Base model, slip ratchet
	S08C*L	Secure Plus, slip ratchet, EN 397 4 point chinstrap
	S08C*R	Wheel ratchet
	S08C*RL	Secure Plus, wheel ratchet, EN 397 4 point chinstrap
	S08C*SH	Concept Miner, slip ratchet, PVC sweatband

Notes: * denotes the helmet shell colour
Fitted with Combi slot
All variants can have brand information presented on a padprint (P) or label (L)
Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Models in Range (Continued):	Product code	Description
	S09C*A	Base model, slip ratchet
	S09C*C	Slip ratchet, with brushed nylon sweatband
	S09C*L	Secure Plus, slip ratchet, EN 397 4 point chinstrap
	S09C*R	Wheel ratchet
	S09C*RL	Secure Plus, wheel ratchet, EN 397 chinstrap
	S09C*RWNP-SH11	With drilled holes, wheel ratchet, Vabon sweatband
	S09C*SH	Concept Miner, slip ratchet, PVC sweatband

- Notes:**
- * denotes the helmet shell colour
 - Fitted with Combi slot
 - All variants can have brand information presented on a padprint (P) or label (L)
 - Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	Concept, vented
Classification:	ANSI Z89.1:2014
Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.
LT	Lower temperature (−30°C)

Test Report: UK models BSI 253/8665690
KSA models BSI 253/8665752 Issue 2

Models in Range:	Product code	Description
	S08C*F	Base model, slip ratchet
	S08C*FSH	Concept Miner, slip ratchet, PVC sweatband
	S08C*LF	Secure Plus, slip ratchet, EN 397 4 point chinstrap
	S08C*RF	Wheel ratchet
	S08C*RLF	Secure Plus, wheel ratchet, EN 397 chinstrap
	S08C*RJ	Roofer wheel ratchet (complete with vent plugs)
	S08C*RWJ	Roofer wheel ratchet (complete with vent plugs), Vabon sweatband

Notes: * denotes the helmet shell colour
Fitted with Combi slot
All variants can have brand information presented on a padprint (P) or label (L)
Secure Plus formerly known as Linesman

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Models in Range (Continued):

Product code	Description
S09C*F	Base model, slip ratchet
S09C*FSH	Concept Miner slip ratchet, PVC sweatband
S09C*LF	Secure Plus, slip ratchet, EN 397 4 point chinstrap
S09C*RF	Wheel ratchet
S09C*RLF	Secure Plus, wheel ratchet, EN 397 4 point chinstrap
S09C*RJ	Roofer wheel ratchet (complete with vent plugs)
S09C*RWJ	Roofer wheel ratchet (complete with vent plugs), Vabon sweatband

* denotes the helmet shell colour

Fitted with Combi slot

All variants can have brand information presented on a padprint (P) or label (L)

Secure Plus formerly known as Linesman

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 17 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories:	Product code	Description
	S30C	2 point Cotton chinstrap
	S30E	2 point Elasticated chinstrap
	S30LY	4 point quick release EN 397 Secure Plus Black Chinstrap (branded)
	S30LBCC	Helmet Lamp Bracket and Cable Clip
	S30VP	Concept vent plugs
	S30Y	4 point quick release EN 397 Secure Plus Black Chinstrap (unbranded)
	S31D	Dry-Tech sweatband
	S31N	Brushed nylon sweatband
	S31P	PVC sweatband
	S31W	Vabon sweatband
	S33/34	Terylene cradle with Dry-Tech sweatband
	S33/35	Terylene Cradle with wheel ratchet and Dry-Tech Sweatband
	S565	Euro accessory clips
	S570	Connect accessory clips
	S589	Retractable eyeshield Clear, Z87 U6
	S589SE	Retractable eyeshield Smoke Grey, Z87 U6 L1.3
	S71CE	Scala X Ear Defenders
	S72CE	Scala XI Ear Defenders
	S55	Contour Visor Carrier
	S800	Contour X, clear polycarbonate face screen, Z87+ D3
	S810	Contour XI, anti-fog, clear polycarbonate face screen, Z87+ D3

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 18 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories: (continued)	Product code	Description
	S50UFL	Universal Fleece Helmet Liner
	S50HVOFC	Frost Cape HV Orange
	S50HVFYFC	Frost Cape HV Yellow
	S50HVOEDFC	Frost Cape HV Orange with Ear Defender Compatibility
	S50HVFYEDFC	Frost Cape HV Yellow with Ear Defender Compatibility
	S50FW	Face Warmer



First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 19 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Range:	1125 Classic								
Product Description:	<p>Safety Helmet with standard peak variants. For versions complying with ANSI Z89.1:2014, there are a number of variations in the build standard of the product, see details below. The range can be fitted with a number of different accessories that are attached via either the Connect or the Euro accessory clips</p> <p>Shell: HDPE, non vented</p> <p>Suspension:</p> <p>Cradle: 6 point Terylene webbing</p> <p>Headband: LDPE with fitted sweatband</p> <p>Sweatband: Brushed Nylon, PVC or Vabon</p> <p>Adjustment system: Wheel ratchet or slip ratchet</p> <p>Chinstrap: EN 397 2 point chinstrap or 4 point chinstrap</p>								
Size range:	<p>Wheel Ratchet headband: 52-64 cm</p> <p>Slip Ratchet headband: 51-63 cm</p>								
Classification:	<p>ANSI Z89.1:2014</p> <table><tr><td>Type I</td><td>Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.</td></tr><tr><td>Class C</td><td>Class C helmets are not intended to provide protection against contact with electrical hazards.</td></tr><tr><td>Class E</td><td>Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.</td></tr><tr><td>LT</td><td>Lower temperature (−30°C)</td></tr></table>	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.	Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.	Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.	LT	Lower temperature (−30°C)
Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.								
Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.								
Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.								
LT	Lower temperature (−30°C)								
Test Report:	BSI 253/8632931, Intertek 102853782CRT-001								

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Models in Range:	Product code	Description
	S03C*A	Base model, slip ratchet
	S03C*L	Secure Plus, slip ratchet, EN 397 4 point chinstrap
	S03C*R	Wheel ratchet
Notes:		
*denotes the helmet shell colour		
Fitted with Combi slots		
All variants can have brand information presented on a padprint (P) or label (L)		
Secure Plus formerly known as Linesman		

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Spares and Accessories:	Product code	Description
	S30C	2 point Cotton Chinstrap
	S30E	2 point Elasticated Chinstrap
	S30L	2 point Leather Chinstrap
	S30Y	4 Point quick release EN 397 Secure Plus Black Chinstrap (Unbranded)
	S30QRC	2 point Quick Release Chinstrap
	S31N	Brushed Nylon Sweatband
	S31P	PVC sweatband
	S33/3	Terylene Cradle with Brushed Nylon Sweatband
	S565	Euro Accessory Clips
	S570	Connect Accessory Clips
	S71CE	Scala X Ear Defenders
	S72CE	Scala XI Ear Defenders
	S50HVOFC	Frost Cape HV Orange
	S50HVFYFC	Frost Cape HV Yellow
	S50HVOEDFC	Frost Cape HV Orange with Ear Defender Compatibility
	S50HVFYEDFC	Frost Cape HV Yellow with Ear Defender Compatibility
	S50FW	Face Warmer
	S51HVV/HVO	Sun Capes

First Issued: 2018-02-05

Latest Issue: 2024-06-25

Effective Date: 2024-06-25

Expiry Date: 2028-07-16

Page: 22 of 28

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Range: **Vison Plus Industrial Safety Helmet**

Product Description: An industrial safety helmet with an injection moulded ABS shell with LDPE headband and 6-point 20mm wide fabric cradle assembly incorporating moulded Polycarbonate visor style eye protection. The visor is designed to be retracted from the wearer's line of sight into a cavity between the shell of the helmet and the cradle. It can fit over prescription spectacles if required and is replaceable by the end user. There are a number of variations in the build standard of the product. The range can be fitted with a number of different accessories attached to the Euro accessory slot.

Shell:	ABS, non-vented.
Cradle:	Fabric webbing
Headband:	LDPE with sweatband
Sweatband:	Dry-Tech (polyester)
Adjustment system:	Wheel ratchet or slip ratchet
Chinstrap anchorages:	2 Point or 4 Point fixing

Size range: Wheel Ratchet headband: 52-64 cm
Slip Ratchet headband: 51-63 cm

Classification: ANSI Z89.1:2014

Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
Class C	Class C helmets are not intended to provide protection against contact with electrical hazards.
Class E	Class E helmets are intended to reduce the danger of contact with higher voltage conductors. Test samples are proof-tested at 20,000 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.
LT	Lower temperature (−30°C)

Test Report: BSI 8900993a1, Intertek 103749767CRT-001

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Classification:	ANSI Z87.1:2015
	Z87+ Personal eye and face protection devices without prescription lenses and with impact protection
	U6 UV filter scale 6

Test Report:	COLTS Z-BKH031918-01-02, Z-BKH061021-01
---------------------	---



First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Verification Certificate

No. VC 684765

Product Specification (continued)

Model:	S06 E-Protect Nexus		
Product Description:	An industrial safety helmet made from wood fibre reinforced polymer with LDPE headband and 6-point 20mm wide cradle assembly. The E-Protect Nexus has vented and non-vented versions and comes in nine coloured shells. Shell: Wood fibre reinforced polymer, vented and non-vented. Cradle: 6-point fabric webbing. Headband: LDPE with sweatband fitted. Adjustment system: Wheel Ratchet Chin strap anchorages: 2 Point chinstrap fitted.		
Size Range:	Wheel Ratchet Headband: 52 – 64 cm		
Classification:	ANSI Z89.1:2014	Type I	Type I helmets are intended to reduce the force of impact resulting from a blow only to the top of the head.
	Class C (vented)		Class C helmets are not intended to provide protection against contact with electrical hazards.
	Class G (non-vented)		Class G helmets are intended to reduce the danger of contact with low voltage conductors. Test samples are proof-tested at 2,200 volts (phase to ground). This voltage is not intended as an indication of the voltage at which the helmet protects the wearer.
Test Report:	1.24.05.53 ANSI ISEA Z89.1 2014		

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Range:	S589/S589C retractable eyeshields	
Product Description:	S589 retractable clear eyeshield for fitting to Nexus and Concept industrial helmets with UV protection and S589 retractable smoked eyeshield for fitting to Nexus and Concept industrial helmets with UV protection and sunglare filter	
Classification:	ANSI Z87.1:2015	
	Z87	Personal eye and face protection devices without prescription lenses and without impact protection
	U6	UV filter scale 6
	L1.3	Nominal light transmittance of 74.5%
Test Report:	ICS T10810-01-1	
Models in Range:	Product code	Description
	S589	Retractable eyeshield Clear, Z87 U6
	S589SE	Retractable eyeshield Smoke Grey, Z87 U6 L1.3

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Range:	S810/S810 Contour face screens	
Product Description:	Contour clear polycarbonate moulded face screens for fitting to Nexus and Concept industrial helmets using a carrier and helmet accessory clips.	
Classification:	ANSI Z87.1:2015	
	Z87+	Personal eye and face protection devices without prescription lenses and with impact protection
	D3	Droplet and splash protection
Test Report:	COLTS Z-BKH050917-01	
Models in Range:	Product code	Description
	S800	Contour X, polycarbonate, moulded, clear face screen using carrier S55, Z87+ D3
	S810	Contour XI, polycarbonate, moulded, anti-fog, clear face screen using carrier S55, Z87+ D3
Spares and Accessories:	Product code	Description
	S55	Contour carrier for use with Concept and Nexus

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16

Verification Certificate

No. VC 684765

Product Specification (continued)

Range:	S590 face screen	
Product Description:	Clear polycarbonate face screens for fitting to Concept industrial helmets using a carrier and helmet accessory clips - 225 mm.	
Classification:	ANSI Z87.1:2015	
	Z87+	Personal eye and face protection devices without prescription lenses and with impact protection
Test Report:	COLTS Z-BKH062718-01, Z-BKH061021-02	
Spares and Accessories:	Product code	Description
	S54CE	Contour carrier for use with Concept and Nexus

First Issued: 2018-02-05
Latest Issue: 2024-06-25

Effective Date: 2024-06-25
Expiry Date: 2028-07-16