

TECHNICAL DATA SHEET

NEXUS VISOR



NEXUS VISOR

The Nexus visor is designed for the toughest of environments, providing protection at extremes of temperatures with anti-scratch/anti-fog coatings and easy-to-use pull down tabs.

FEATURES AND BENEFITS

- Optical class 1 with a wide field of vision
- Impact Rating A - High energy impact; 6mm, 0.86g ball travelling at 425mph (685kph)
- K rated Anti-Scratch outer coating for lasting durability
- N rated Anti fog coating for use in a wide range of environments
- UV Protection EN170 2-1,2
- Available in Smoked for Sunglare protection to EN172 5-3
- Use over spectacles without compromising comfort or visibility
- Compatible with ear defenders and half mask respirators
- Choice of two mounting options



MARKETS

- Construction, Building, Civil Engineering.
- Utilities, Maintenance, Energy, Oil, Gas and Mining.
- Logistics and Transportation.
- Automotive and Aerospace.
- Chemicals, Pharmaceutical.
- FMCG, Food and Drink, Pulp and Paper, Packaging, Recycling, Agriculture.
- Maritime, Port Authorities, Dockyard.



Arm for S585
Accessory Clip



Arm for S565
Accessory Clip

SPECIFICATION: EYE SHIELDS

Product Options	Product	Colour	Material	Screen Length (Visible length when fitted)	Weight (S565)	Weight (S585)
	Standard	Clear	2mm Polycarbonate	100mm	108.4g	113.9g
	Smoked	Tinted				

EUROPEAN AND INTERNATIONAL STANDARDS WITH OPTIONS

Product	EN 166:2001:Personal Eye Protection									
	F - Low Energy Impact	B - Medium Energy Impact	A - High Energy Impact	1 - Optical Class	T - High Speed Particles at extremes of temperature	8 - Electric Arc	2C-1,2 - UV radiation protection – good colour recognition	2-1,2 - UV radiation protection	4-5 - Infrared radiation protection	5-2,5 - Sunglare filters - dark
Standard Clear	●	●	●	●	●	●	●	●	●	●
Smoked	●	●	●	●	●	●	●	●	●	●

Care and Maintenance

Storage

Can be stored and transported in original packaging at ambient temperature (0°C to + 30°C). Can be stored in the dark for up to 5 years. Storage in direct sunlight, extremes of temperature, and in a fashion that is liable to distort is not recommended.

Lifetime:

These products have been designed to have an in-use life of up to 5 years. It is recommended that after 5 years the product is replaced. Excessive wear and tear can considerably reduce the lifespan of the product. Replace if structure or visibility is impaired.

Cleaning:

Clean using warm soapy water and soft cloth. Care must be taken to avoid scratching.

Disposal:

Recycling is preferred when possible. Look out for the recycling symbol for material category.

Packaging

Product	Individual product packaging dimensions	Individual bagged weight including product	Outer box dimensions	Outer box weight including product	Number of products in outer packaging
Standard Clear	(H) 611.5 x (W) 480.49mm	TBC		TBC	10
Smoked	(H) 611.5 x (W) 480.49mm	TBC	TBC	TBC	10

Product Codes and Bar Codes

Product code	Description	Case bar code	Unit bar code/GTIN
S601-9969641	Nexus Eye Shield Clear S65 arms and S65 clip	5056375447150	05056375447143
S602-9969642	Nexus Eye Shield Smoked S65 arms and S65 clip	5056375447174	05056375447167



Centurion Safety Products Ltd
T: +44 (0) 1842 754266
F: +44 (0) 1842 765590
A: 21 Howlett Way, Thetford,
Norfolk, IP24 1HZ, United Kingdom
centurionsafety.co.uk

version number 001
06/2024