

## TECHNICAL DATASHEET

# NEXUS T2

**S07**

ANSI Type II recreational styled Safety Helmet with 'Micro Peak' for optimum visibility. Designed for high-risk environments offering protection from impacts to the top, side and rear of the head.

## SPECIFICATION

Helmet Options	Non vented & vented wheel ratchet
Size	53 - 63cm
Weight	560g
Peak	Micro (20mm)
Packaging	5 per colour. Box size 28 x 22 x 50cm. Weight 3.2kg

## MATERIALS

Shell	ABS
Liner	Reinforced Expanded Polypropylene Liner
Liner Pad	Polyester, PU Foam, Nylon wool (Machine Washable 40°C)
Headband	LDPE (Low Density Polyethylene)
Sweatband	Polyester, PU Foam, Nylon wool (Machine Washable 40°C)
Wheel Ratchet	Acetal with HDPE Straps, Black Foam 3mm

## SAFETY STANDARDS

		Nexus T2 (Vented)	Nexus T2 (Non Vented)
ANSI/ISEA Z89.1-2014 (R2019) Type I	4.2.3 Class C (Conductive 0V a.c.)	X	
	7.1.1 Flammability	X	X
	7.1.2 Force Transmission	X	X
	7.1.3 Apex Penetration	X	X
	7.1.4.3 Class E (20,000V a.c.)		X
	7.2.1 Impact Energy Attenuation	X	X
	7.2.2 Off-Centre Penetration	X	X
	7.2.3 Chin Strap	X	X

## PRODUCT CODES

Product Code	Description
S07EWRT	Nexus T2 - White - Non - Vented
S07EWRFT	Nexus T2 - White - Vented
S07EKRT	Nexus T2 - Black - Non - Vented
S07EKRFT	Nexus T2 - Black - Vented
S07EBRT	Nexus T2 - Blue - Non - Vented
S07EBRFT/5	Nexus T2 - Blue - Vented
S07EYRT	Nexus T2 - Yellow - Non - Vented
S07EYRFT	Nexus T2 - Yellow - Vented
S07EWRFT/5	Nexus T2 - White - Vented 5 PK
S07EWRFT/MPS	Nexus T2 - White - Vented 5 PK MPS
S07EBRFT/MPS	Nexus T2 - Blue - Vented 5 PK MPS



## FEATURES

- ✓ Meets ANSI Type II Standard.
- ✓ Premium Grade ABS provides high performance and optimal strength to weight ratio for the ultimate wearer protection.
- ✓ The washable padded sweatband and liner offer superb absorption and comfort, staying fresh at up to 40°C.
- ✓ 4 Point Chinstrap providing comfort & support

## MARKETS

- Construction and Building, Civil Engineering
- Utilities, Maintenance, Sustainable Energy, Oil, Gas & Mining
- Logistics & Transportation
- Automotive & Aerospace
- Engineering and Chemicals & Pharmaceutical
- FMCG, Food & Drink, Pulp + Paper, Packaging, Recycling & Agriculture
- Petroleum

**CORPORATE BRANDING AVAILABLE**  
 FRONT | BACK | SIDES

## CARE & MAINTENANCE

### Storage:

Can be stored and transported in their original cartons at ambient temperatures (0°C to + 30°C) May be stored in the dark for up to 5 years. Do not store in direct/ high heat or sunlight as this may distort the shell

### Lifetime:

The Centurion helmet has an in-use life of up to 5 years. Excessive wear and tear can considerably reduce the lifespan of the product.

### Cleaning:

Clean using warm soapy water and soft cloth.

### Disposal:

Recycling is preferred when possible. Look out for the recycling symbol for material category.



## HELMET COLOURS

COLOUR				
	White (W)	Blue (B)	Yellow (Y)	Black (K)
RAL	9010	5026	1018	9005
Pantone	WHITE	2768	109	BLACK

## ACCESSORIES & SPARES

Product Code	Description
S31EP	Padded Sweatband Heat Pressed Black Spare
S31EC	Liner Comfort Pad Black Spare
S34K	Slotted Kit Brackets Spare
S34HR	Complete Headband assembly Spare
S601	Nexus Visor - Clear
S602	Nexus Visor - Smoked
S725	Sana 25 Helmet Mounted Ear Defenders
S730	Sana 30 Helmet Mounted Ear Defenders
S734	Sana 34 Helmet Mounted Ear Defenders
S31DCHP	Kalis Bright Yellow Dry Cooling Helmet Pad
S31DCHS	Kalis Bright Yellow Dry Cooling Helmet Sweatband
S50UFL	Universal Fleece Helmet Liner
S50HVOFC	Frost Cape HV Orange
S50HVEDFC	Frost Cape HV Yellow with Ear Defender Compatibility
S51HVO	Bright Orange Helmet Sun Cape
S51HVV	Bright Yellow Helmet Sun Cape
S55	Contour Visor Carrier
S800	Contour X General Purpose Face screen 2C-1,2 1BT 3 9
S810	Contour XI Multi-Purpose Face screen 2C-1,2 1BT 3 8-1-0 9

